

# Declaration of Performance

Gyproc® Moisture Resistant



<b>1 Unique identification code of the product type:</b>	Gyproc Moisture Resistant
<b>2 Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):</b>	Gyproc Moisture Resistant: 12.5mm, 15mm EN 520 - H1
<b>3 Intended use/s:</b>	Plasterboard lining
<b>4 Manufacturer:</b>	British Gypsum Registered in England 734396 East Leake, Loughborough, Leicestershire LE12 6HX Tel: +44 (0) 115 945 1000
<b>5 Authorised representative:</b>	N/A
<b>6 System/s of AVCP:</b>	System 4
<b>7 Designated standard:</b> <b>Approved body/ies:</b>	EN 520:2004+A1:2009 N/A
<b>8 European Assessment Document:</b> <b>European Technical Assessment:</b> <b>Technical Assessment Body:</b> <b>Approved body/ies:</b>	N/A N/A N/A N/A

<b>9 Declared performance/s:</b>	The characteristics in the table below apply to all products mentioned in 2 above.
----------------------------------	--

Essential characteristics	Performance	Harmonised technical specification
Shear strength ( $\downarrow$ )	NPD	EN 520:2004+A1:2009
Reaction to Fire (R2F)	A2-s1, d0	EN 520:2004+A1:2009
Water vapour permeability ( $\mu$ )	10	EN 520:2004+A1:2009
Longitudinal flexural strength (F)	550N (12.5mm) 650N (15mm)	EN 520:2004+A1:2009
Transverse flexural strength (F)	210N (12.5mm) 250N (15mm)	EN 520:2004+A1:2009
Impact resistance <sup>1</sup> ( $\rightarrow$ I)	See manufacturer's literature	EN 520:2004+A1:2009
Direct airborne sound insulation <sup>1</sup> (R)	See manufacturer's literature	EN 520:2004+A1:2009
Acoustic absorption <sup>1</sup> ( $\alpha$ )	See manufacturer's literature	EN 520:2004+A1:2009
Thermal resistance (as conductivity) ( $\lambda$ )	0.19W/mK	EN 520:2004+A1:2009

<sup>1</sup> These characteristics are system dependent and will be provided in manufacturer's literature based upon intended use.

# Declaration of Performance

Gyproc® Moisture Resistant



UK  
CA

**10 Appropriate Technical Documentation and/or Specific Technical Documentation:**

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulations (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dean O'Sullivan, Managing Director, British Gypsum

East Leake 18/05/2023

Place and date of issue