

UK Declaration of Performance

Inno-Torch

1000.UKDoP.IT.002 1001.UKDoP.IT.002

Unique identification code of the product-type: **Inno-Torch**
 Intended use/es: **Thermal insulation for buildings**
 Manufacturer: **EcoTherm Insulation (UK) Ltd, Harvey Road, Basildon, SS13 1QJ**
 System/s of AVCP: **System 4 (Reaction to fire), System 3 (Other Properties)**
 Designated technical specification: **BS-EN 13165:2012+A2:2016**
 UK Assessment/Notified body/ies: **University of Salford:1145, B.I.T.S: 1334, BBA: 0836**

Essential characteristics		Performance
Thermal resistance	Thermal resistance R_D ((m ² .K)/W)	d _N 30mm 1.10 d _N 40mm 1.45 d _N 50mm 1.85 d _N 60mm 2.20 d _N 70mm 2.55 d _N 80mm 3.20 d _N 90mm 3.60 d _N 100mm 4.00 d _N 120mm 5.00 d _N 130mm 5.40 d _N 140mm 5.83 d _N 150mm 6.25
	Thermal conductivity λ_D (W/(m.K))	Flat board - Pembridge Plant 1000 d _N < 80mm 0.027 d _N 80-119mm 0.025 d _N ≥ 120mm 0.024 Flat board – Selby Plant 1001 d _N < 80mm 0.027 d _N 80-119mm Not manufactured d _N ≥ 120mm 0.024
	Thickness tolerance	T2
Reaction to fire	Reaction to fire	F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD

UK Declaration of Performance

Inno-Torch

1000.UKDoP.IT.002 1001.UKDoP.IT.002

Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance R_D ((m².K)/W)	Thermal resistance as table above												
	Thermal conductivity λ_D (W/(m.K))	Flat board - Pembridge Plant 1000 <table><tr><td>$d_N < 80\text{mm}$</td><td>0.027</td></tr><tr><td>$d_N 80\text{-}119\text{mm}$</td><td>0.025</td></tr><tr><td>$d_N \geq 120\text{mm}$</td><td>0.024</td></tr></table> Flat board – Selby Plant 1001 <table><tr><td>$d_N < 80\text{mm}$</td><td>0.027</td></tr><tr><td>$d_N 80\text{-}119\text{mm}$</td><td>Not manufactured</td></tr><tr><td>$d_N \geq 120\text{mm}$</td><td>0.024</td></tr></table>	$d_N < 80\text{mm}$	0.027	$d_N 80\text{-}119\text{mm}$	0.025	$d_N \geq 120\text{mm}$	0.024	$d_N < 80\text{mm}$	0.027	$d_N 80\text{-}119\text{mm}$	Not manufactured	$d_N \geq 120\text{mm}$	0.024
	$d_N < 80\text{mm}$	0.027												
	$d_N 80\text{-}119\text{mm}$	0.025												
	$d_N \geq 120\text{mm}$	0.024												
	$d_N < 80\text{mm}$	0.027												
$d_N 80\text{-}119\text{mm}$	Not manufactured													
$d_N \geq 120\text{mm}$	0.024													
Durability characteristics	NPD													
Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1													
Deformation under specified compressive load and temperature conditions	NPD													
Determination of the aged values of thermal resistance and thermal conductivity	λ_D 0,024, 0.025, 0,027 W/m·K													
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150												

UK Declaration of Performance

Inno-Torch

1000.UKDoP.IT.002 1001.UKDoP.IT.002

Tensile / Flexural strength	Tensile strength perpendicular to faces	TR80
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Continuous Glowing Combustion	Glowing Combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

EU Regulation 305/2011, as retained in UK law, and as amended by SI no. 465/2019 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2019) and SI no. 1359/2020 (the Construction Products (Amendment etc.) (EU Exit) Regulations 2020.)

Signed for and on behalf of the manufacturer by:



.....
Aiveen Kearney
Managing Director
Pembroke, Selby, England, UK
Date signed: 03/03/2023
Issue Number: 002



UK Declaration of Performance

Inno-Torch

1000.UKDoP.IT.002 1001.UKDoP.IT.002