



UK Declaration of Performance

Inno-Fix

1000.UKDoP.IF.003 1001.UKDoP.IF.003

Unique identification code of the product-type: Inno-I

Intended use/es: Thermal insulation for buildings

Manufacturer: EcoTherm Insulation (UK) Ltd, Harvey Road, Basildon, SS13 1QJ

System/s of AVCP: System 4 (Reaction to fire), System 3 (Other Properties)

Designated technical specification: BS-EN 13165:2012+A2:2016

UK Assessment/Notified body/ies: University of Salford: 1145, B.I.T.S: 1334, BBA: 0836

Essential characteristics		Performance
Thermal resistance	Thermal resistance R _D ((m².K)/W)	d _N 25mm 1.10 d _N 30mm 1.35 d _N 40mm 1.80 d _N 50mm 2.25 d _N 60mm 2.70 d _N 70mm 3.15 d _N 80mm 3.60 d _N 90mm 4.05 d _N 100mm 4.50 d _N 120mm 5.45 d _N 130mm 5.90 d _N 140mm 6.35 d _N 150mm 6.80 d _N 160mm 7.25
	Thermal conductivity λ_D (W/(m.K))	d _N 25-160mm 0.022
	Thickness tolerance	T2
Reaction to fire	Reaction to fire	F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD
	Durability of thermal resistance and thermal conductivity against ageing/degradation	NPD
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance R _D ((m².K)/W)	Thermal resistance as table above
	Thermal conductivity λD (W/(m.K))	0.022
	Durability characteristics	NPD
	Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1





UK Declaration of Performance

Inno-Fix

	Deformation under specified compressive load and temperature conditions	NPD	
	Determination of the aged values of thermal resistance and thermal conductivity	λD 0,022 W/m·K	
Compressive strength	Compressive stress or compressive strength	CS(10\Y)150	
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR40	
Durability of compressive strength against ageing / degradation	Compressive creep	NPD	
Waterpermeability	Short term water absorption	NPD	
	Long term water absorption	NPD	
	Flatness after one sided wetting	NPD	
Watervapourpermeability	Watervapourtransmission	NPD	
Acoustic absorption index	Sound absorption	NPD	
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD	
NPD: No Performance Determined			

Signed for and on behalf of the manufacturer by:

risen dez

Aiveen Kearney Managing Director

Pembridge, Selby England, UK Date signed: 03/03/2023

Issue Number: 003