

Superglass Acoustic Roll 12

Acoustic Roll 12 is a lightweight, non-combustible glass mineral wool insulation roll. The product is designed to provide thermal and acoustic insulation for the in a number of applications including internal floors and partitions.

Manufactured at a minimum density of 12kg/m³.

Thickness (mm)	Length (m)	Width (mm)	Area (m ²)	Packs per pallet	Code
100	9.50	1200	11.40	24	6080
100	9.50	2x600	11.40	24	6087

Environmental

Acoustic Roll 12 has a Generic A+ BRE Green Guide Rating. Classified as having zero ODP (Ozone Depletion Potential) and zero GWP (Global Warming Potential), they are also CFC and HCFC free.

Durability

Acoustic Roll 12 is non-hygroscopic, will not rot, degrade or sustain vermin and will not encourage the growth of mould, bacteria or fungi.

Standards

Acoustic Roll 12 is manufactured to comply with the requirements of CE Marking 93/68/EEC and Technical European Harmonised Standards BS EN 13162:2012, BS EN 13172: 2012. Also manufactured in accordance with BSI Quality Assurance Standard BS EN 9001: 2012.

Fire Classification

All Superglass products are deemed non-combustible and have a fire classification of A1 (the highest possible rating) when tested to BS EN 13501-1 Reaction to Fire.

Vapour Resistance

Acoustic Roll 12 possesses negligible vapour resistance allowing vapour to pass freely through the insulation.

Handling & Storage

Acoustic Roll 12 is supplied compression packed in polythene to provide short term protection. For long term protection, the product must be stored indoors or under a waterproof covering in order to protect against weather damage. Acoustic Roll 12 should not be left permanently exposed to the elements.

Superglass Insulation Ltd

Thistle Industrial Estate, Kerse Road, Stirling, Scotland, FK7 7QQ

Tel: 01786 451170 Email: technical@superglass.co.uk

www.superglass.co.uk