

Product Data Sheet

Application: Internal Walls and Floors

Isover Acoustic Partition Roll (APR 1200)



Acoustic Insulation for Internal Stud Walls and Floors

Isover Acoustic Partition Roll (APR 1200) is a glass mineral wool roll that can provide a level of acoustic performance in metal and timber internal stud walls as well as timber joist separating and internal floors. To support ease of installation, it is supplied in 600mm widths for an easy friction fit between stud centres.

Features and Benefits



When used in British Gypsum internal wall and floor elements, Isover Acoustic Partition Roll (APR 1200) can contribute towards a measurable reduction in airborne sound transmission. Refer to the British Gypsum White Book System Selector for system-specific data. The SpecSure® warranty confirms British Gypsum proprietary systems will perform as specified for the lifetime of the building. For further details, please visit british-gypsum.com/technical-advice/specsure.



Achieves a Euroclass A1 Reaction to Fire classification, according to EN 13501-1.



Manufactured from up to 82% recycled glass with all electric equipment in the plant powered by 100% renewable electricity. For further details visit isover. co.uk/CSR



Straightforward to handle, cut and install with minimal waste (off-cuts can be reused). Friction fits between 600mm stud centres.

Key Considerations

When using Isover Acoustic Partition Roll (APR 1200), you need to satisfy yourself that use of the product meets all relevant national Building Regulations and guidance as well as local, national and other applicable standards relevant for your construction or application, including requirements in relation to fire and applicable height restrictions.

Please refer to the following product documents:

- Declaration of Performance available at isover.co.uk/products/isover-acoustic-partition-rollapr-1200
- Safe Use Instruction Sheet available at isover.co.uk/healthandsafety

Product Specification

Product code	Thickness (mm)	Length (m)	Width (m)	Roll area (m²)	Rolls per pallet	Pallet area (m²)
5200625577	25	20.00	2 x 0.60	24.00	24	576.00
5200625578	50	13.00	2 x 0.60	15.60	24	374.40
5200625579	65	10.00	2 x 0.60	12.00	24	288.00
5200625580	75	12.20	2 x 0.60	14.64	24	351.36
5200625581	100	9.17	2 x 0.60	11.00	24	264.10

Characteristics

Fire	Euroclass A1 Reaction to Fire classification according to EN 13501-1.	Certification	CE marked to Bs in 18162. CE marked to EN 18162. Designation code: MW-EN 18162-T1.	
Environmental	All Isover products are manufactured under Environmental Management System - ISO 14001:2015.	Handling, Storage.	, , , , , , , , , , , , , , , , , , , ,	
Recycled Content	Manufactured from up to 82% recycled glass.	Health and Safety		
		Quality	All Isover products are manufactured under Quality	
			Management Standard - ISO 9001.	



Isover

Saint-Gobain Isover UK Limited, Saint-Gobain House, East Leake, Loughborough, Leicestershire, LE12 6JU.

Customer Service -Order Placement and Enquiries

Tel: 0800 0322 555 Email: isover.customerservice@saint-gobain.com

Technical Support Team

Email: isover.technical@saint-gobain.com

isover.co.uk

Published date: 10 July 2025

Isover reserves the right to amend or revise product specification without notice. The information in this publication is correct at the time of publication. The information herein should not be read in isolation as it is meant only as guidance for the user, who should always ensure that they are fully conversant with the products and systems being used and their subsequent installation prior to the commencement of work.

For an up-to-date library of product information, users should visit the website at isover.co.uk $\,$

Saint-Gobain Isover UK Registered in England. Company Number 10442670.

 $Registered\ Offices: Saint-Gobain\ House, East\ Leake,\ Loughborough,\ Leicestershire,\ LE12\ 6JU.$